

# Bekasecure® post

The Bekasecure posts have a unique design and guarantee higher security, important rigidity and easy installation.





## **Benefits**

The Bekasecure posts have a unique patented profile and are available with or without base plate. The panels are secured by using a continuous cover plate and specific stainless steel security bolts.

- The post's design and high yield strength steel provides the ultimate in high security, rigidity and ease of installation. The open profile of the post allows for electrical or fibre optic cabling
- Patented system

#### **Profile**

- Post profile "Omega", 140 x 135 x 4.00mm (up to 6m fence height)
- With a double range of holes 10 x 20mm for the fixation of panels and cover plates
- Specific metal cap
- I/V: 43.6cm<sup>3</sup>

## Accessories/options

- Bent arms
- Welded foot plate
- Cover plates for intermediary and corner posts
- One-way security bolts for the fixation of panels, cover plate and metal caps

## Coating technique




Hot-dip galvanised inside and outside (505g/m² – both sides combined) and polyester plastic coated (minimum 60 microns).

### Colours

Green RAL 6005. Other colours are available on request.

### Product detail



Bekasecure <sup>®</sup> post range			
Panel height (mm)	Post length (mm)	Base plate (mm)	Cover plate length (mm)
To put in concrete			
3001.2	4050	-	3050
3674.3	4800	-	2060 + 1730
4004.5	4800	-	2060 + 2060
With base plate			
4004.5	4050	230 x 230 x 15	2060 + 2060
6011.1	6030	300 x 300 x 20	2060 + 2060 + 2060

## Compatible products

- Securifor® Flat
- Securifor® 2D
- Securifor® 4D

**Europe:** Blokkestraat 34b, B-8550 Zwevegem Tel: B: +32 56 73 46 46

**USA:** 3309 SW Interstate 45, Ennis, TX 75119 Tel: +1 972 878 7000 Middle East: P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 **Africa:** B10, Bergriver Business Park, Paarl, 7646 Tel: +27 021 868 7300

