




Izifix® posts

Posts

Profiled post, without fixators, compatible with 3D and 2D panels types. Easy and fast to install. Ideal for fence erectors looking for reliability and cost-efficiency.

Product detail



BENEFITS

- No fixators needed to maintain panels
- Long linguets for efficient stability of the panel into the post
- Angles up to 180° with the same post
- Slope installation with 100 mm steps
- No need to cut 3D profile to install the panel
- Cost-effective system

Profile

- Dimensions: 75 x 50 mm
- Slot every 100 mm
- Slope installation: 100 mm steps
- Yield strength: Min. 250 MPa
- Betafence branding on the front of the post
- Supplied with caps

Tools

- Tensioning tool to ensure a correct and easy installation

Options

- Base plate

Coating technique

Fully galvanised inside and outside. Finished with a polyester coating of min. 60 micron.



Colors

Green RAL 6005, white RAL 9010, black RAL 9005 and anthracite RAL 7016.
Other colors on request.

Compatible products

- Nylofor 3D
- Nylofor 3D Pro (XL)
- Nylofor 3D Essential
- Nylofor 3D Light
- Nylofor 2D*
- Nylofor 2DS*
- Bekafor Classic

ASSORTMENT IZIFIX		
Post length in mm	Fence height in mm (on baseplate)	Fence height in mm (in concrete)
1075	1030	630
1275	1230	830
1475	-	1030
1575	1530	-
1775	1730	-
1975	1930	1530
2175	-	1730
2475	2430*	1930
2575	-	2030

Europe
Blokkestraat 34b
B-8550 Zwevegem
Tel: B: +32 56 73 46 46

USA
3309 SW Interstate 45
Ennis, TX 75119
Tel: +1 972 878 7000

Middle East
P.O. Box 293517 DAFZA, Building E 5,
Block A 8th Floor, Office 802
Tel: +971 04 6091122

Africa
B10, Bergriver Business Park
Paarl, 7646
Tel: +27 021 868 7300